

# GT5 SERIES AMPLIFIERS

THE JBL® GT5 AMPLIFIER LINE includes a dedicated Class D subwoofer amplifier and two full-range amplifiers that have been engineered to deliver low distortion and optimum system tuning at a great value.

Each model includes a 12dB-per-octave variable electronic crossover, with the subwoofer amplifier offering a variable bass EQ and the

full-range amplifiers offering a selectable bass EQ. All three models feature full-range preamp outputs to facilitate easy system-building and wiring architecture. The GT5 amps also feature common-dimension footprints for all three models, which minimizes the amount of space occupied, thus optimizing multiple-amplifier mounting applications.



[www.jbl.com](http://www.jbl.com)

Andrew Shandro – Team Trek/Volkswagen/JBL. Photo by Sterling Lorence.

# GT5 SERIES AMPLIFIERS

# SPECS



## GT5-A402

120-Watt 2-Channel Full-Range Amplifier

- 40W RMS x 2 channels at 4 ohms and  $\leq 1\%$  THD + N\*
- 60W RMS x 2 channels at 2 ohms and  $\leq 1\%$  THD + N\*
- Signal-to-noise ratio: 85dBA (reference 1W into 4 ohms)\*
- Signal-to-noise ratio: 101dBA (reference rated power into 4 ohms)
- THD + N: 0.05% (rated power @ 4 ohms)
- Built-in variable electronic crossover
- Selectable bass EQ
- Frequency response: 10Hz – 100kHz (–3dB)
- Total peak power: 240 Watts
- RCA low-level preamp inputs
- RCA low-level preamp outputs
- Dimensions (L x W x H): 7-1/2" x 9-1/4" x 2-1/8"
- \* CEA-2006A compliant

## GT5-A604

320-Watt 4-Channel Full-Range Amplifier

- 60W RMS x 4 channels at 4 ohms and  $\leq 1\%$  THD + N\*
- 80W RMS x 4 channels at 2 ohms and  $\leq 1\%$  THD + N\*
- Signal-to-noise ratio: 85dBA (reference 1W into 4 ohms)\*
- Signal-to-noise ratio: 102dBA (reference rated power into 4 ohms)
- THD + N: 0.05% (rated power @ 4 ohms)
- Built-in variable electronic crossover
- Variable bass EQ on rear channel
- Frequency response: 10Hz – 100kHz (–3dB)
- Total peak power: 640 Watts
- RCA low-level preamp inputs
- RCA low-level preamp outputs
- Dimensions (L x W x H): 12" x 9-1/4" x 2-1/8"
- \* CEA-2006A compliant

## GT5-A3001

300-Watt Mono Subwoofer Amplifier

- 175W RMS x 1 channel at 4 ohms and  $\leq 1\%$  THD + N\*
- 225W RMS x 1 channel at 2 ohms and  $\leq 1\%$  THD + N\*
- 300W RMS x 1 channel at 1 ohm and  $\leq 1\%$  THD + N
- Signal-to-noise ratio: 95dBA (reference 1W into 4 ohms)\*
- Signal-to-noise ratio: 120dBA (reference rated power into 4 ohms)
- THD + N: 0.05% (rated power @ 4 ohms)
- Built-in variable electronic crossover
- Variable bass EQ
- Frequency response: 10Hz – 330Hz (–3dB)
- Total peak power: 600 Watts
- RCA low-level preamp inputs
- RCA low-level preamp outputs
- Remote bass-level control included
- Dimensions (L x W x H): 12" x 9-1/4" x 2-1/8"
- \* CEA-2006A compliant



# JBL

THE OFFICIAL BRAND OF LIVE MUSIC.

Harman Consumer Group, Inc.  
250 Crossways Park Drive  
Woodbury, NY 11797  
516.255.4JBL (4525) Fax: 516.682.3556  
www.jbl.com

A Harman International Company

Features, specifications and appearance are subject to change without notice.

JBL is a registered trademark, and GT Series is a trademark, of Harman International Industries, Incorporated.

Designed, edited and digitally produced by the Harman Consumer Group Marketing & Design Center, Woodbury, NY.

© 2007 Harman International Industries, Incorporated. All rights reserved.  
Part No. 6TOAMPPI9/07 Printed in USA 9/07

Andrew Shandro – Team Trek/Volkswagen/JBL. Photo by Sterling Lorence.

# www.jbl.com